


1. ALL RESISTORS IN OHMS AND 0.5W.
2. ALL CAPACITORS IN MICROFARADS UNLESS OTHER PREFIX MARKED, THEN REPLACE PREFIX (MICRO) IN UNIT (MICROFARAD) WITH MARKED PREFIX. ALL CAPACITORS 25V (MINIMUM VOLTAGE RATING) UNLESS MARKED OTHERWISE.
3. ALL VOLTAGES IN VOLTS.
4. ALL POTS, R19 TO R22: 100KB.
5. TRANSISTOR Q1: MPSA13.
6. TRANSISTOR Q2: 2N5088.
7. TRANSISTOR Q3: 2N5086.
8. ZENER DIODE D1: 1N5244B.
9. LAST REFERENCED DESIGNATION ON SCHEMATIC:  
R22, C10, Q3, D1, J4, P3.

		Rickenbacker International Corp. 3895 S. Main Street Santa Ana, Ca. 92707 Tel: 714-545-5574 Fax: 714-754-0135	
		SCHEMATIC, PREAMP RB30, RB60, AND RB120	
SCALE	NA	CHECKED BY	DRAWN BY
DATE	3/8/89	J. HALL	K. MASCARENHAS
SIZE	B	DRAWING NO 19326	