


1. ALL RESISTORS IN OHMS. ALL RESISTORS 0.25W UNLESS MARKED OTHERWISE.
2. ALL CAPACITORS IN MICROFARADS UNLESS OTHER PREFIX MARKED, THEN REPLACE PREFIX (MICRO) IN UNIT (MICROFARAD) WITH MARKED PREFIX. ALL CAPACITORS 25V (MINIMUM VOLTAGE RATING) UNLESS MARKED OTHERWISE.
3. ALL VOLTAGES IN VOLTS.
4. TRANSISTORS Q1, Q2: 2N5086.
5. TRANSISTORS Q3, Q4: 2N5210.
6. TRANSISTOR Q5: MPSA06.
7. TRANSISTOR Q6: MPSU56.
8. TRANSISTOR Q7: TIP41B.
9. TRANSISTOR Q8: MPSU06.
10. TRANSISTOR Q9: E15030.
11. TRANSISTOR Q10: E15031.
12. TRANSISTORS Q11, Q12, Q13: TIP36C.
13. TRANSISTORS Q14, Q15, Q16: TIP35C.
14. IC Q17: 4N28.
15. DIODE D1: 1N4148.
16. DIODES D2, D3, D4, D5: 1N4002.
17. ZENER DIODES D6, D7: 1N5244B.

18. LABEL(S) NOT USED: R25, R38.
19. LAST REFERENCED DESIGNATION ON P.C. BOARD:  
R41, C14, Q17, D7, L1, P1, J1, W7.

		Rickenbacker International Corp. 3895 S. Main Street Santa Ana, Ca. 92707 Tel: 714-545-5574 Fax: 714-754-0135	
		<b>COMPONENT LAYOUT, POWER AMP RG180, RB120</b>	
SCALE	x1	CHECKED BY	DRAWN BY
DATE	2/28/89	J. HALL	K. MASCARENHAS
SIZE	DRAWING NO		19336
B			